

Cast Steel Parallel Slide Valve - Flanged PN16

LV 7860

Flanged PN16, Carbon Steel BS EN 10213 Gr. GP240GH WCB Body, TDA 58 Copper Nickel Silicon Alloy Seat Rings, Stainless Steel Stem, Exfoliated Gland Packing, Designed to BS EN 1984



Pressure / Temperature Specifications

Pressure	PN16
Temperature (Min/Max)	0°C to 400°C

Pressure / Temperature Specifications

°C	120	150	200	250	300	350	400
Bar	16	15.2	14.5	13.3	12.2	11.3	10.2

Material Specifications

Body	Carbon Steel BS EN 10213 Gr. GP240GH WCB
Cover	Carbon Steel BS EN 10213 Gr. GP240GH WCB
Seat Rings	TDA58 Copper Nickel Silicon Alloy
Doors	TDA58 Copper Nickel Silicon Alloy
Stem	Stainless Steel BS EN 10088-3 1.4057
Gland Packing	Exfoliated Graphite

Dimensions

Size	A	B	C	Kg
2"	178	368	200	19.0
2½"	190	431	200	25.0
3"	203	490	250	32.0
4"	229	580	315	45.0
5"	254	743	400	74.0
6"	267	810	400	88.0
8"	292	1012	530	142.0
10"	330	1250	530	232.0
12"	356	1454	530	370.0

